

CCTV

0

IP Corner-Mount Camera

EV-N4506-2S4Q

The ENFORCER IP Corner-Mount Camera equipped with Sony STARVIS[™], that provides high quality color saturation when recording at night. The Corner-Mount Camera has a discreet, low-profile appearance and a wide-angle lens, making it perfect for elevators and office corners.

Features

- ¹/_{2.8}" 5MP Sony STARVIS™ CMOS
- H.265, H.264/MJPEG, Tri-stream IP Camera
- Max. 30FPS/Full HD 5MP (2592x1944)
- Remote access via web browser
- Network Bandwidth Control
- Event Alarm, E-mail, FTP Function
- 30 Covert IR LEDs for discreet monitoring in the dark
- True Day & Night function with ICR mechanism
- Vandal-resistant metal front panel
- 3DNR & WDR
- 12VDC, PoE (IEEE802.3af)

Sony STARVIS[™] CMOS

Typical CMOS Low-light







3D Digital Noise Reduction:

3DNR Off

3DNR On





Simulated images

SECO-LARM® U.S.A., Inc. 16842 Millikan Avenue, Irvine, CA 92606 **Phone:** (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326 **Website:** www.seco-larm.com **Email:** sales@seco-larm.com



Specifications

0

Туре		Corner-Mount Camera
CMOS		¹ / _{2.8} " 5MP Sony STARVIS™ CMOS
Video encoding		H.265, H.264, MJPEG
Resolution		5MP (2592x1944)
DNR	2DNR	- Yes
	3DNR	
WDR		Yes
# of IR LEDs		30 Covert (940nm)
Lens		2.8mm
Viewing angle		157°
Minimum illumination		0.01Lux
F Stop		1.6
Gamma correction		0.45
S/N Ratio		50dB
Gain control		Auto
White balance		Auto
Operating voltage		12VDC, PoE (IEEE802.3af)
Current draw (IR Off)		140mA max.
IP Rating		IP65
Operating temperature		14°~122° F (-10°~50° C)
Dimensions		7 ¹ / ₂ "x5 ¹ / ₂ "x1 ¹¹ / ₁₆ " (190x140x43 mm)
Weight		13.75-oz (390g)

F© (€ 🚳

Copyright © 2024 SECO-LARM U.S.A, Inc. All rights reserved. All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM[®] **ENFORCER[®]** CRIMEBUSTER[®] CBA[®] **SLI[®]**

PI_EV-N4506-2S4Q_240131.docx